

## PORTABLE MOTOPUMP (LOMBARDINI 23 HP)




- The Pump is first non-priming motopump. The Pumps do not need any priming system the suction hose restarts self-suction again in couple of seconds even if it comes out of the water several times.
- All the pump parts are manufactured in our factory, therefore there is no spare parts supplying problem.
- Multipurpose pump. In addition to firefighting, our Pumps can operate smoothly in dirty water, flood water, oily water, sewage and seawater.
- The pump body made by two separated parts. In case of any failure it can easily unscrew the body and easily maintenance.
- The Pumps have two different unique protection systems to prevent damage to the pump and the engine in case of any hard metal and similar substances get in the suction hose during the operation.

- Suction at geographical 10 meters depth. Although the phrase is suction, due to the nature of our patented system pushing the water up with the help of a propeller, that means there is no loss flow rate up to 7 meters.
- Ory working capability. Working dry does not effect the operation. It won't give any damage to pump or engine.
- The pumps have corrosion-resistant series of material and long-lasting operation performance by advanced aluminum technology.
- The Pumps have ISO 9001, TSE, CE and EN 14466 Portable Pumps certificates.

## 2 CYLINDER AIR COOLED NUMBER OF CYLINDER COOLING SYSTEM BORE X STROKE 90,00 X 75,00 (mm) PISTON DISPLACEMENT 17 kW - 23,1 HP OUTPUT FUEL TYPE FUEL TANK CAPACITY 3 LT/HR (%50 STROKE) FUEL CONSUMPTION OIL TANK CAPACITY 3 LT ELECTRIC MECHANIC SPECIAL PATENTED SUCTION SYSTEM SUCTION SYSTEM SINGLE END SUCTION CENTRIFUGAL PUMP **PUMP TYPE** STORZ TYPE 4" (100 mm) STORZ TYPE SUCTION TYPE AND DIA PUMP 2-1/2" (65 mm) DISCHARGE NUMBER DISCHARGE VALVE BALL VALVE DRY WEIGHT WET WEIGHT 140 KG OVERALL LENGTHXWIDTHXHEIGHT 600 X 850 X 750



## P1 DIESEL MOTOPUMP PERFORMANCE CURVE





order@kozmaksan.com.tr